



TECHNICAL SPECIFICATION

Our Aura combines architectural minimalist aesthetics with high-performance engineering. Featuring interchangeable optics, a selectable 5-CCT DIP switch, and smooth Triac dimming, it is the ideal versatile solution for commercial, retail, and modern residential spaces requiring flexible and precise accent lighting.

SPECIFICATIONS

- Housing Material: Heavy-duty Aluminum
- Cylinder Track Light
- Lens inter-changeable
- 5CCT Selectable: 2700K / 3000K / 3500K / 4000K / 5000K
- Beam Angle: 24° / 36° / 60°
- LED/CRI: COB CRI90
- Input voltage: AC 120V (60Hz)
- Application: Dry Location
- Dimming Method: Triac Dimming 120V
- Installation Method: Track mounted (H-Type / J-Type ahead)
- ETL Certified

AURA-2-10W		AURA-3-15W	
 Dimension & Wattage Ø 2,56" – 10W 845 – 1020lm		 Dimension & Wattage Ø 3,38" – 15W 1315 – 1620lm	
AURA-3-20W	AURA-3-25W	AURA-3-30W	
 Dimension & Wattage Ø 3,38" – 20W 1745 – 2130lm	 Dimension & Wattage Ø 3,38" – 25W 2060 – 2460lm	 Dimension & Wattage Ø 3,94" – 30W 2250 – 2750lm	



CCT Selectable

2700K  5000K

FINISHES

Fixture:  
 Black White

ACCESSORIES (LENS)



1. Trim Type

- ☐ AURA-2-10W = Aura 2,56" (845-1020lm)
- ☐ AURA-3-15W = Aura 3,38" (1315-1620lm)
- ☐ AURA-3-20W = Aura 3,38" (1745-2130lm)
- ☐ AURA-3-25W = Aura 3,38" (2060-2460lm)
- ☐ AURA-3-30W = Aura 3,38" (2250-2750lm)

2. Color Temperature

☐ 5CCT = CCT Selectable

3. Finish

- ☐ B = Black
- ☐ W = White

4. Dimming

☐ TRIAC = Leave Blank



Example: AURA-3-15W-5CCT-B = Aura Track Light 3,38" – 15W (1315 – 1620lm) – CCT Selectable – Finish Black – Triac Dimming